

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 2016-06-06 Revision date: 2025-09-09 Supersedes: 2023-01-30 Version: 5.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Fleetcool EX EG Concentrate
Product code : CC2739, CC2739 X, CC2740, CC2740 X, CC2741, CC2741 X, CC2742, CC2742 X

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Premix Antiboil/Antifreeze Coolant

1.4. Supplier's details

Manufacturer

Fleetguard
1200 Fleetguard Road
Cookeville, TN, 38506
USA
T 1-800-22-FILTER (1-800-223-4583)

Distributor

Fleetguard
Canadian Distributor
11751 181 St.
Edmonton, AB, T5S 2K5
Canada
T 1-780-455-2151

1.5. Emergency phone number

Emergency number : Chemtrec 1-800-424-9300 (Within Continental U.S.)
Chemtrec 703-527-3887 (Outside the U.S.)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Acute toxicity (oral), Category 4
Skin sensitization, Category 1
Reproductive toxicity, Category 2
Specific target organ toxicity, Single exposure, Category 1

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Harmful if swallowed
May cause an allergic skin reaction
Suspected of damaging fertility or the unborn child.
Causes damage to organs (central nervous system, kidneys) (oral).

Precautionary statements (GHS) :

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapours/spray.

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves, protective clothing, eye protection, face protection.
If exposed or concerned: Call a poison center or doctor.
If swallowed: Call a poison center or doctor if you feel unwell.
Rinse mouth.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice or attention.
Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)Weight
Ethylene glycol	Ethylene glycol 1,2-Dihydroxyethane / Ethane-1,2-diol / 1,2-Ethanediol / Ethanediol / GLYCOL / Glycol / Monoethylene glycol	CAS-No.: 107-21-1	80 – 100
Sodium mercaptobenzothiazole	Sodium mercaptobenzothiazole 2(3H)-Benzothiazolethione, sodium salt / 2-Mercaptobenzothiazole, sodium salt / Sodium benzothiazol-2-yl sulphide / Sodium 2-mercaptobenzothiazole / Mercaptobenzothiazole sodium salt / 2(3H)-Benzothiazolethione, sodium salt (1:1)	CAS-No.: 2492-26-4	0.1 - 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: IF SWALLOWED : Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide (CO2). Water spray. Sand.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Use water spray to cool exposed surfaces. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

For non-emergency personnel

No additional information available

For emergency responders

Environmental precautions	: Avoid release to the environment. Prevent entry to sewers and public waters.
---------------------------	--

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not breathe gas, mist, vapors, spray. Avoid contact with skin and eyes. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Keep in original containers. Keep in a cool, well-ventilated place. Store locked up.
- Specific end uses : Premix Antiboil/Antifreeze Coolant.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol (107-21-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethylene glycol
ACGIH® TLV® TWA	25 ppm (vapor fraction)
ACGIH® TLV® STEL	10 mg/m ³ (inhalable particulate matter, aerosol only)
ACGIH® TLV® STEL	50 ppm (vapor fraction)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2024
Sodium mercaptobenzothiazole (2492-26-4)	
USA - NIOSH - Occupational Exposure Limits	
US-NIOSH chemical category	SK: DIR(COR)-SEN Aug 2014

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Safety glasses or goggles are recommended when using product.
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Pink
Odour	: No data available
Odour threshold	: No data available
pH	: 10.4
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 325 °F /162.8 °C
Flash point	: No data available
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: 1.118
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

Ethylene glycol	
Boiling point	197.3 °C (at 1013 hPa)
Flash point	115 °C (open cup)
Auto-ignition temperature	398 °C
Vapour pressure	0.1 hPa (at 20 °C)
Particle characteristics	No data available

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Sodium mercaptobenzothiazole	
Boiling point	103 °C
Flash point	> 93 °C
Vapour pressure	32 hPa (at 25 °C)
Particle characteristics	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Incompatible materials.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Fleetcool EX EG Concentrate	
ATE US (oral)	516.322 mg/kg bodyweight
Ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	10600 mg/kg (Source: Health Canada)
LD50 dermal	9530 mg/kg
LC50 inhalation rat	> 2.5 mg/l (Exposure time: 6 h Source: ECHA_API)

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethylene glycol (107-21-1)	
LD50, human, oral	1570 mg/kg (ingestion of ethylene glycol is more hazardous to humans than animals (Source: Health Canada))

Sodium mercaptobenzothiazole (2492-26-4)	
LD50 oral rat	1476 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 7940 mg/kg (Source: EPA_HP V)
LC50 inhalation rat	> 8.2 mg/l (Exposure time: 6 h Source: EPA_HP V)

Skin corrosion/irritation	: Not classified. pH: 10.4
Serious eye damage/irritation	: Not classified. pH: 10.4
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.

Ethylene glycol (107-21-1)	
NOAEL (chronic, oral, animal/male, 2 years)	1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Causes damage to organs (central nervous system, kidneys) (oral).

Ethylene glycol (107-21-1)	
STOT-single exposure	Causes damage to organs (central nervous system, kidneys) (oral).
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.

Fleetcool EX EG Concentrate	
Viscosity, kinematic	No data available

Ethylene glycol (107-21-1)	
Viscosity, kinematic	14.465 mm ² /s

Sodium mercaptobenzothiazole (2492-26-4)	
Viscosity, kinematic	No data available

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: Toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Ethylene glycol (107-21-1)	
LC50 - Fish [1]	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
EC50 - Crustacea [1]	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 96h - Algae [1]	6500 – 13000 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [2]	6500 – 13000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
NOEC chronic crustacea	4.2 mg/l

Sodium mercaptobenzothiazole (2492-26-4)	
LC50 - Fish [1]	0.3 – 1.1 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	1.9 – 5.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	3.8 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: IUCLID)
EC50 96h - Algae [1]	0.3 mg/l (Species: Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

Fleetcool EX EG Concentrate	
Persistence and degradability	Not established.

Ethylene glycol (107-21-1)	
Persistence and degradability	Rapidly degradable

Sodium mercaptobenzothiazole (2492-26-4)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Fleetcool EX EG Concentrate	
Bioaccumulative potential	Not established.

Ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water	-1.36

Sodium mercaptobenzothiazole (2492-26-4)	
Partition coefficient n-octanol/water	-0.46

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified.
Fluorinated greenhouse gases : No

Fleetcool EX EG Concentrate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Other information : Avoid release to the environment. No other effects known.

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14 Transport information

In accordance with DOT / TDG

14.1. UN Number

UN-No. (DOT) : Not regulated
UN-No. (TDG) : Not regulated

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated
Proper Shipping Name (TDG) : Not regulated

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not regulated

TDG
Transport hazard class(es) (TDG) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated
Packing group (TDG) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Phosphonic acid, methyl-, mono[3-(trihydroxysilyl)propyl] ester, monosodium salt	CAS-No. 84962-98-1
--	--------------------

Fleetcool EX EG Concentrate

Safety Data Sheet


According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Phosphonic acid, methyl-, monomethyl ester, monosodium salt	CAS-No. 73750-69-3
Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S	
Sodium nitrite	CAS-No. 7632-00-0
All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories except for:	
Phosphonic acid, methyl-, monomethyl ester, monosodium salt	CAS-No. 73750-69-3

15.2. International regulations

No additional information available

15.3. State regulations

 **WARNING:** This product can expose you to Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 2025-09-09
Issue date : 2016-06-06
Other information : None.
Prepared by : Nexreg Compliance Inc.
Prepared for : Fleetguard

Indication of changes:			
Section	Changed Item	Change	Version
SDS	SDS update	Modified	2.0
SDS	SDS update GHS Classification	Modified	3.0
SDS	SDS update GHS classification Manufacturer Information	Modified	4.0
SDS	SDS update GHS Classification	Modified	5.0

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.